

## Snatch Blocks | 2 – 8 Ton | 418 & 419 | Single Sheave (Hook & Shackle Top)

### New Improved Light Champion

- Forged alloy heat treated hooks.
- Forged steel swivel tees, yokes and shackles.
- Hook and shackle assemblies on 4-1/2" through 14" sizes can be interchanged.
- Can be furnished with bronze bushing or roller bearings.
- Opening feature permits insertion of rope while block is suspended from gin-pole.
- 3" thru 18", 418 and 419 blocks have exclusive bolt retaining spring to assure no lost bolts.
- Can be furnished with S-4320 hook latch.
- Pressure lube fittings.
- 3" – 10" feature dual rated wireline sheaves.
- Fatigue rated.

**418 With Hook**

**419 With Shackle**

**404 Tail Board**


### Specifications

Sheave Diameter (in.)	Bearing Code	Stock No.			Wire Rope Size (in.)	Working Load Limit (ton)*	Weight Each (lbs.)			Rep. Sheave Stock No.	Rep. Latch Stock No.
		418 with hook	419 with shackle	404 Tail Board			418 with hook	419 with shackle	404 Tail Board		
** 3	BB	—	109091	—	5/16 – 3/8	2	—	4	—	460147	—
** 3	BB	108038	109037†	102016	5/16 – 3/8	2	5	4	3	460147	1096421
** 4 1/2	BB	108065	109064	102025	3/8 – 1/2	4	12	12	7	2000232	1096468
6	BB	108127	109126	102098	5/8 – 3/4	8	27	28	15	460815	1096562
8	BB	108225	109224	102169	5/8 – 3/4	8	33	34	21	461164	1096562
10	BB	108323	109322	102230	5/8 – 3/4	8	41	42	29	461805	1096562
12	BB	169169	202961	178890	5/8	8	48	49	36	462270	1096562
12	BB	108421	109420	102301	3/4	8	48	49	36	462289	1096562
16	BB	108608	109607	—	7/8	15	130	135	—	4100065	1096609

\*Ultimate Load is 4 times the working load limit.

\*\*Available in Bronze Bushed only. 3" and 4 1/2" have self-lubricating Bronze Bushing.

† Fitted with 1 1/4" ID Swivel Eye.

‡ May be furnished in other rope sizes.

Note: When ordering, please specify: size, block number, hook or shackle, bronze bushed or roller bearing, and wire rope size.

Green shading reflects rental inventory.