



THE LIFTING EXPERTS

(800) 878-7305

www.RentLGH.com

Rentals@RentLGH.com

420 Lbs. | Beamer 2000 (00101) | Clamp Anchorage Connector

Model 00101



Fixed Clamp

Fits beam flanges up to 1.25" thick

Specifications

Standards:

OSHA 1926 Subpart M & 1910 ANSI Z359.18-17 & A10.32-12
Type A Anchorage Connector

Materials:

Bronze, Aluminum & Stainless Steel

Performance:

- Maximum Users: 1
- 5,000 lbs. MBS (Minimum Breaking Strength)

Notes:

- Minimum service temperature: -30° F
- Beamer 2000 must be installed so no risk exists for it to come off of beam
- Can be used overhead or at foot level with appropriate big boss lanyard
- Never use in vertical applications; for use in steel I or H beams only

Applications

Personal Fall Arrest:

Beamer Anchors may be used in Personal Fall Arrest applications to support:

- MAXIMUM 1 PERSONAL FALL ARREST SYSTEM (PFAS)
Structure must withstand loads applied in th directions permitted by the system of at least 5,000 lbs.
- Maximum free fall is 6', unless used in combination with equipment explicitly certified for extended free fall
- Applicable D-rings: Dorsal

Restraint:

Beamer Anchors may be used in Restraint applications

Restraint systems:

- Prevent workers from reaching the leading edge of a fall hazard.
Always account for fully deployed length of lanyard/SRL
- Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs
- No free fall is permitted
- May only be used on surfaces with slopes up to ⁴/₁₂ (vertical/horizontal)
- Applicable D-rings: Dorsal, Chest, Side & Soulder

Specifications			
Product Code	Worker Capacity (lbs.)	Description	Weight (lbs.)
00101	130-420	Compatible beam flange: 3 1/2 - 14	4



Green shading reflects rental inventory.